





-  EN1143-1  
Burglary protection
-  EN15659  
Fire protection (option)
-  VdS  
Grade VKB
-  ECB-S  
Grade VKB  
+ LFS60P (option)
-  ISO  
Class EN 6
-  DIN  
4102 (light fire protection)



-  Domestic insurable  
by arrangement
-  Commercial insurable  
up to EUR 375.000

Fig. Safe EWS1600KB, hinge right  
E-Lock Kaba Code Combi B, K-Lock S+G 1 key guide tube 2 bits, 1 inside locker, 1 shelf

| Model      | Outside dimensions<br>h x w x d (mm) |            | Inside dimensions<br>h x w x d (mm) |            | SH | Volume<br>(l) | Weight<br>(appr. kg) |
|------------|--------------------------------------|------------|-------------------------------------|------------|----|---------------|----------------------|
| EWS0849KBR | 848                                  | 645 x 565  | 695                                 | 495 x 320  | 1  | 110           | 665                  |
| EWS0850KBR | 848                                  | 810 x 725  | 695                                 | 660 x 480  | 1  | 220           | 935                  |
| EWS1000KBR | 1003                                 | 810 x 725  | 850                                 | 660 x 480  | 2  | 269           | 1060                 |
| EWS1200KBR | 1193                                 | 810 x 725  | 1040                                | 660 x 480  | 2  | 329           | 1220                 |
| EWS1600KBR | 1538                                 | 810 x 725  | 1385                                | 660 x 480  | 3  | 439           | 1505                 |
| EWS1901KBR | 1883                                 | 810 x 725  | 1730                                | 660 x 480  | 4  | 548           | 1790                 |
| EWS1903KBR | 1883                                 | 1110 x 725 | 1730                                | 960 x 480  | 4  | 797           | 2230                 |
| EWS1902KB  | 1883                                 | 1110 x 725 | 1730                                | 960 x 480  | 4  | 797           | 2270                 |
| EWS1904KB  | 1883                                 | 1415 x 725 | 1730                                | 1265 x 480 | 4  | 1050          | 2720                 |

SH = Shelf

Please add 60 mm to the listed outside depth for mountings.

## [ Safes ]

## [ Type EWSKB ]

In addition to the EWS series features, EWSKB series safes provide additional protection against burglars armed with diamond core drills thanks to their special structural wall design. Safes weighing less than 1.000 kg must be anchored.

## [ Product information ]

- Hinge** DIN right – model designation R (EWS1902KB, EWS1904KB double-doored)  
option: DIN left
- Door opening angle** 180°
- Body** double-walled, reinforced, with core drill protection, filled with armoured, high resistant barrier material
- Door structure** triple-walled, reinforced, with core drill protection, filled with armoured, high resistant barrier material, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance
- Locking mechanism** three-way moving boltwork with large steel bolts, protected by glass plate with additional emergency re-lockers, fix engaging steel bolts on the hinge side
- Anchoring** fitted for floor anchoring  
anchoring bolts and shields are supplied for EWS0849KB, EWS0850KB  
option: additional anchoring holes (customer specifies position)
- Alarm connection** VdS-certified cable channels to allow connection to a burglar alarm system
- Colour** outside RAL 7035 light grey + RAL 7045 tele grey1, inside RAL 7035 light grey  
option: special colour according to RAL
- Lock** safes in grades IV and higher have to be equipped with at least 2 certified locks  
any set of locks (from VdS class 2 up) is possible
- Equipment** shelf adjustable (height setting 69 mm, EWS0849 60 mm)  
option: additional shelf, inside locker  
option (from EWS0850KB up): drawer, pull-out shelf
- Accessories** option: fire protection door rebate seals, alarm switch set, interior lighting
- Option** additional certified fire protection LFS60P – except models:  
EWS0849KB, EWS1902KB, EWS1904KB  
bolted version (without fire protection) – assembly on site

## [ Equipment options ]



EWS0849KB EWS0850KB EWS1000KB EWS1200KB EWS1600KB EWS1901KB EWS1903/1902KB EWS1904KB